

Petroleum Suction/ Discharge Tank Truck Hose 150 PSI

Features

- Oil and weather resistant Construction
- Reinforcement: High tensile tire cord plies, Helix wire
- Cover: Black Neoprene
- Tube: Black Nitrile
- Operating Temperatures: -40°F to 200°F (-40°C to 93°C)

Typical Application

- Recommended for use to handle the bulk transfer of petroleum products
- Handles most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals

Fittings

- Crimp-on, KC nipple, cam & groove coupling and hammer unions



Part #	Hose I.D.	Hose O.D.	Work. Press. (PSI)	Bend Radius (in.)	Wt./ Ft. (lbs.)
PSD20	1 1/4	1.688	150	6	.70
PSD24	1 1/2	1.938	150	8	.84
PSD32	2	2.531	150	10	1.21
PSD40	2 1/2	2.938	150	13	1.48
PSD48	3	3.5	150	16	1.76
PSD64	4	4.625	150	18	3.64
PSD96	6	6.813	150	22	4.17
PSD128	8	9.063	150	28	6.02



Petroleum Suction/ Discharge Tank Truck Hose 250 PSI

Features

- Oil and weather resistant Construction
- Reinforcement: High tensile tire cord plies, Helix wire
- Cover: Black Neoprene
- Tube: Black Nitrile
- Operating Temperatures: -40°F to 200°F (-40°C to 93°C)

Typical Application

- Recommended for use to handle the bulk transfer of petroleum products
- Handles most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals

Fittings

- Crimp-on, KC nipple, cam & groove coupling and hammer unions



Part #	Hose I.D.	Hose O.D.	Work. Press. (PSI)	Bend Radius (in.)	Wt./ Ft. (lbs.)
PSD25032	2	2.656	250	12	2.15
PSD25048	3	3.656	250	18	3.41
PSD25064	4	4.719	250	20	4.87
PSD25096	6	6.875	250	26	8.18
PSD250128	8	9.063	250	30	14.35
PSD250160	10	12	250	60	20.49
PSD250192	12	14.125	250	100	26.49



WORLD RIG SUPPLY
Connecting the world